



| |
|----------------------|
| Project Name: |
| Landscape Architect: |
| Part #: |
| Quantity: |
| Comments: |

PALM BATTEN KITS

SPECIFICATION SHEET

Features

- **PRE-FABRICATED** - Pre-notched, pre-cut and includes 5 layers of burlap backing
- **WIDELY SPECIFIED** - Parks, corporate campuses, DOT, schools
- **FAST** - 5-10min install by one person
- **MADE IN THE USA**

Specifications

PBKM

- (3) 1 1/2"x3" 1/2"x12" (2"x4" wood) battens with 5 layers of burlap backing that overlaps edges and with (2) staple guides for banding, pre-notched to accept 2"x4" braces
- (2) 9/16" x 4.5' stainless steel bands with tensioning and locking screw/clamp

PBKR

- (3) 1 1/2"x3" 1/2"x12" (2"x4" wood) battens with 5 layers of burlap backing that overlaps edges and with (4) staple guides for banding, pre-notched to accept 2"x4" braces
- (2) 1"x6' polyester bands w/2500lb break strength, 0% stretch
- (2) Tensioning ratchets to secure battens

*** *Root Ball Anchoring System available for palms with solid root balls with up to 30' clear trunk. See Root Ball Anchoring Systems specification sheet for additional information. ****



Ordering Information

Example: PBKR

| Series | Banding Option |
|--------|--|
| PBK | M - 9/16" x 4.5' Stainless Steel Bands |
| | R - 1" x 6' Polyester Band w/ Ratchets |